

DH-PFM979-1S4P

4-way Power Splitter Cable




Technical Specification			
Main Line	Conductor (Diameter and Material)	30/0.15 mm copper wires 42/ 0.12 mm tinned copper wire	
	Outer Diameter	3.5 mm (0.14")	
	Sheath Material	PVC	
	Sheath Color	Black	
Branch	Conductor (Diameter and Material)	2 × 26 AWG copper wire	
	Outer Diameter	3.0 mm (0.12")	
	Sheath Material	PVC	
	Sheath Color	Black	
DC Male	Dimensions	Φ5.5 mm × Φ2.1 mm (Φ0.22" × Φ0.08")	
DC Female	Dimensions	Φ5.5 mm × Φ2.1 mm (Φ0.22" × Φ0.08")	
Length	Total Length (Main Line + Branch)	370 mm ± 10 mm (14.57" ± 0.39")	
	Branch	220 mm ± 10 mm (8.66" ± 0.39")	
Others	Insulation Resistance	≥ 20 mΩ	
	Conductor Resistance	≤1Ω	
	Operating DC Voltage and Current	12 V, 5 A	
	Plug/Unplug Times	500 times	
	Packaging Method	1 pcs in 1 PE bag, 300 bags in 1 box	
	PE Bag Dimensions	100 mm × 245 mm (3.94" × 9.65")	
	Protective Box Dimensions	400 mm × 330 mm × 200 mm (15.75" × 12.99" × 7.87")	
	Weight	33.4 g (0.07 lb) per bag	

- \cdot 1-to-4, 5.5 mm \times 2.1 mm DC power splitter cable is quick and easy to plug in, allowing multiple devices to receive power at the same time.
- · Rated voltage of the whole line is 12 V, and the rated current is 5 A.
- \cdot Eco-friendly, it meets the RoHS and REACH standards.
- \cdot Safe and reliable, it has a long lifespan as it is fireproof, resistant to high temperatures and can be plugged in and out multiple times.

Ordering Information			
Туре	Model	Description	
Cable Series	DH-PFM979-1S4P	4-way Power Splitter Cable	

Dimensions (mm[inch])



Rev 002.000

© 2023 Dahua. All rights reserved. Design and specifications are subject to change without notice.

The images, specifications and information mentioned in the document are only for reference, and might differ from the actual product.