

DH-PFM979-LDS

DC Power Cable with Female Connector



Technical Specification			
Cable	Conductor (Diameter and Material)	2 × 20 AWG copper wire	
	Insulation Material	PVC	
	Insulation Color	Red, black	
	Length	250 mm ± 10 mm (9.84" ± 0.39")	
DC Female	Dimensions	Φ5.5 mm × Φ2.1 mm (Φ0.22" × Φ0.08")	
Others	Operating Voltage and Current	12 V, 5 A	
	Plug/Unplug Times	500 times	
	Insulation Resistance	≥ 20 mΩ	
	Conductor resistance	≤1Ω	
	Packaging Method	10 pcs in 1 PE bag, 160 bags in 1 box	
	PE Bag Dimensions	100 mm × 245 mm (3.94" × 9.65")	
	Protective Box Dimensions	480 mm × 400 mm × 200 mm (18.90" × 15.75" × 7.87")	
	Weight	80 g (0.18 lb) per bag	

- \cdot 5.5 mm \times 2.1 mm DC female splitter cable splits to a bare wire that makes connecting convenient.
- \cdot Rated voltage of the whole line is 12 V, and the rated current is 5 A.
- · Eco-friendly, meets the RoHS and REACH standards.
- · Safe and reliable, long lifespan and fireproof, resistant to high tem peratures and can be plugged in and out multiple times.

Ordering Information			
Type	Model	Description	
Cable Series	DH-PFM979-LDS	DC Power Cable with Female Connector	

Dimensions (mm[inch])

